



Village of Wrightstown Department of Public Works

P.O. Box 227
101 Washington Street
Wrightstown, WI 54180

Phone – 920-532-0434
Fax – 920-532-0433
www.vil.wrightstown.wi.us

Concrete Driveway Specification

Note: A 48 hour notice during normal business hours is required to the Public Works Department prior to the start of any work (cutting curb entrance, forming and pouring concrete, and/or paving the driveway).

Per Village Typical Standard Specifications:

Driveways for single family homes shall be a maximum width of 30 feet at the face of the future or existing concrete sidewalk. The maximum driveway width, including the flare, at the back of the future or existing concrete curb shall be a maximum width of 33 feet.

Driveways for duplex family homes shall contain a maximum width of 39 feet at the face of the future or existing concrete sidewalks. The maximum driveway width, including the flare, at the back of the future or existing concrete curb shall be a maximum width of 42 feet.

The sidewalk panel in the driveway should be 5 feet wide and 6 inches thick.

The driveway apron should also be 6 inches thick, and have a flare of 3 feet.

No reinforcement rods are to be placed in the driveway apron or the sidewalk panel.

The sidewalk should have a slope of ¼” per foot for a 5 foot wide sidewalk panel. The rear side of the sidewalk panel should be no greater than 6 inches above the height of the curb in a 16.5 foot right of way. This will vary depending on the width of the right of way.

If you are installing a culvert and driveway for access on to a County Road or a State Highway, you must call the Brown or Outagamie County Highway Department or the Wisconsin Department of Transportation office in Green Bay prior to any work.

Builders are required to notify their concrete sub-contractor of driveway and sidewalk panel requirements.

If you have any questions please call 920-532-0434.

